



# Mppt 12kw Hybrid Inverter 400-1000V Single Phase Hybrid Inverter

#### **Basic Information**

Place of Origin: China
Brand Name: Qiyuan
Certification: CE, IEC
Model Number: GC12K-B400

Minimum Order Quantity: 10

Price: USD/CNY, Unit
Packaging Details: wooden case
Delivery Time: 1-2 months
Payment Terms: L/C, T/T

Supply Ability: 500 set per month



## **Product Specification**

Product Name: MPPT Hybrid Solar Inverter
 Type: Hybrid Solar Inverter
 Application: Solar Power System Home

Input Voltage: 200-1000V DCOutput Power: 1~12kW

• Output Voltage: 110V/220V/230V/240V

Output Frequency: 50Hz/60HzOutput Waveform: Prue Sine Wave

Output Current: 0~75AOutput Type: MultipleEfficiency: >97%

 Protection: Overlaod Over-heat, over Tempereture And Short Circuit, Overvoltage, overcharge

Weight: 28kgWarranty: 5 Years

#### **Product Description**

This Single-phase Hybrid Inverter is suitable for North America use, applicable for villa, communication base station, nomadic area, farm, residential power station, field power supply

#### 1. Advanced

- \* Maximum efficiency up to 98.2%
- \* 4 independent MPPT design.
- \* Distributed virtual power station management mode.
- \* Remote monitoring of PC and mobile phones.

#### 2. Flexible

- \* The model covers 6-12kVA, with unified apprearance design.
- \* Wide battery input range, compatible with a variety of lithium batteries and lead-acid.

### 3. Reliable

- \* Battery reverse connect protection, the charge and discharge are controlled by intelligent software to improve the battery life.
- \* Input and output lightning protection, PV arcing detection.
- \* Discharge at full power and disconnect the charger automatically when the battery is full.
- \* Off grid full power output, transient 1.5 times overload, soft start mode, with air conditioning, water pump and other loads.
- \* Insulation detection, leakage battery, ground fault detection, island protection to prevent electric shock.

#### 4. Design

- \* Elegant appearance, convenient wiring.
- \* IP65 design, natural cooling, external fan free design, low noise, improved service life.

Input (PV)				
Max. PV Input Power	7.8KW	10.4KW	13KW	15.6KW
Max. PV Input Voltage		50	V	
Start Voltage	120V			
MPP Voltage Range	125V~500V			
Rated MPPT Voltage Range	360V			
Max. Input Current per MPPT	12A			
No. of MPPT/String	4/1			
Output (AC)				
Max. Output Current	27.3A	36.4A	45.4A	50A
Rated Power	6kVA	8kVA	10kVA	12kVA
Rated Voltage	230V, L + N+PE			
Grid voltage / range	240/211~264V			
Operating Voltage Range	176V~270V			
Rated Frequency	50Hz/60Hz			
Power Factor	1			
THDi	< 3%			
	Output (E			
Rated Power	6kVA	, 8kVA	10kVA	12kVA
Rated Voltage		220~240/11	0~120 Vac	
Rated Current	27.3A	36.4A	45.4A	50A
Rated Frequency		50Hz/		
Automatic Switching Time	<20ms			
Overload Capability	120%, 10S / 150%, 0.02S			
THDU		<2%		
11120	Battery	· · · · · · · · · · · · · · · · · · ·	70	
Battery Voltage Range		85~4	·00V	
Charge/Discharge Current	80A/80A			
Battery type	Lithium			
Communication	CAN/RS485			
GGGaller.	Efficien			
Max. DC Efficiency	98.2%			
European Efficiency	97.2%			
MPPT Efficiency	99.9%			
Battery Charge/Discharge				
Efficiency	95.5%			
Communication				
Display		LC	D	
Communication	RS48!	RS485/CAN/DRM, Optional: Wifi/LAN		
	Standa		-	
Certificates		C		
55153.55	General D			
Dimensions (W x H x D )		530 x 660	x 200 mm	
Weight	30kG			
Operation Temperature	-25°C~+60°C			
Colling Method	Forced air cooling			
Protection Level	<u> </u>	IP65		
Noise		<35dB		
Max. Operation Altitude	5000M (derate above 2000M)			
Relative Humidity	0~95%			
Ficiality U-30 /6				

Power Consumption	<3W	

# Ningbo Qiyuan New Energy Co., Ltd

18858073356

tony@qygen.com

batteriesback-up.com