

China

Qiyuan

1

ESS500-380-1290

USD/CNY, Unit

2 sets per month

container

1-2 months

## 51.2v Outdoor BESS Solar System 500kwh Container By ESS

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification: CE, IEC, MSDS, UN3536
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: L/C, T/T
- Supply Ability:



## **Product Specification**

Enclosure:	Container, Or Customized	
Capacity:	500KWH Up To 1.37 MWH	
<ul> <li>PCS Power:</li> </ul>	500KW	
Battery:	LiFePo4	
Module:	51.2V 105AH	
<ul> <li>Output Voltage:</li> </ul>	380/400/415VAC	
• Discharge:	0.5C/1C	
• HVAC:	Yes	
<ul> <li>Fire System:</li> </ul>	Yes	
Dimension:	20 Feet Container With Shipping Certificate	
<ul> <li>Shipping:</li> </ul>	Battery In The Container	
• UN Code:	UN3536	
<ul> <li>Highlight:</li> </ul>	outdoor bess solar system, 500kwh container by ess, 51.2v bess solar system	

Our Product Introduction

## **Product Description**

ESS series BESS system provides integrated energy storage technology, serves perfectly for commercial and industrial energy storage application.

- Provide a cost-effective way to store excess energy generated by renewable sources like wind and solar farms.

- Can store excess electricity generated by renewable energy sources such as solar or wind farms, allowing it to be used at a later time when these sources are not available.

- BESS can provide backup power during outages or extreme weather events, reducing the need for costly distribution upgrades or emergency generators.

- Assist in load leveling and grid support, helping to balance fluctuations in electricity demand throughout the day and reduce congestion on the grid.

- Bess can improve power quality by smoothing out voltage fluctuations that may otherwise disrupt equipment operations.

- Easy to install, making them a popular choice for businesses and homeowners looking for reliable energy storage systems.

Model	ESS500-380-1290	ESS500-380-1350
Rated output power	500KW	500KW
Rated grid voltage	380/400/415V	
Input voltage range	320~460VAC	
Output voltage range	380/400/415VAC	
Frequency	50/60HZ	
AC pattern	3W+N+PE	
Grid switching time	<20ms	
System voltage	768	810
Battery module model	51.2V210Ah	
Battery cluster capacity	161.3	172
No. of paralleled clusters	8	
EMS	Yes	
Dry pipe fire extinguishing	Yes	
Fire alarm	Yes	
Fire alarm	Yes	
HVAC	Yes	
Access control	Yes	
Remote control	Yes	
Peak-valley calculation	Yes	
Communication	CAN,RS485	
Protection value	IP54	
PCS unit cooling	Forced air	
Working temperature	-30~55°C	
Maintenance	External maintenance	
Dimension	6058*2400*2900	
Weight MT	24	26

Ningbo Qiyuan New Energy Co., Ltd

18858073356

tony@qygen.com

batteriesback-up.com