



## 5KW 400AH Domestic Battery Energy Storage LiFePo4 Power Stack Battery

## **Basic Information**

Place of Origin: ChinaBrand Name: Qiyuan

• Certification: CE, IEC, MSDS, UN38.3

Model Number: TDD5K-400AH

• Minimum Order Quantity: 10

Price: USD/CNY, Unit
Packaging Details: wooden case
Delivery Time: 1-2 months
Payment Terms: L/C, T/T

Supply Ability: 100 set per month



## **Product Specification**

• Battery Type: LiFePO4 Battery

• Warranty: 3 Years

Application: Home Storage System

Rated Voltage: 48VOutput Power: 5KW

• Capacity: 100AH To 1200Ah

Color: Black&White Shell Or Customized

Type: Deep Cycle BatteryTerminal: Copper Terminal


Cycle Life: More Than 2000 Cycles

Material: Eco FriendlyDesign Life: 8-10 Years

• Highlight: 5kw Domestic Battery Energy Storage,

 ${\bf 400AH\ Domestic\ Battery\ Energy\ Storage},$ 

LiFePo4 power stack battery



## **Product Description**

This product specification applies to the company's lithium iron phosphate battery pack, which is suitable for invert er, photovoltaic invert er, UPS applications. The specification, size, performance, maintenance and test method of the product are as specified.

Item	Specifications	Remarks
Model number	TDD-512-52AH	
Rated voltage (V)	51.2 * N	
Rated capacity (Ah)	52AH	25C 0.5C Discharge
Maximum charging voltage (V)	56*N (configurable)	
Maximum protection voltage for charge (V)	58.4 * N	
Minimum protection voltage V	40*N	
Maximum charging current (A)	50	
Standard charging current (A)	25	
Maximum continuous discharge current (A)	50	
Peak discharge current (A)	75	Within 5S
Number of cell cycle lives	6000	
Ambient temperature for charging (° C)	0 ~ 45	
Discharge operating environment temperature (° C)	- 20 ~ 50	
Ambient humidity	0 ~ 95%	
Protection level	IP43	

Noise dB	0				
Control box parameter	Control box parameters				
Product model number	TDDK102-512-50				
Standard DC voltage range VDC	102 ~ 512				
Control box maximum current A	50				
Ac input voltage VAC	90~265V				
Elevation m	4000				
Power distribution switch	There are				
Display	5"				
Communication method	RJ45, RS485, CAN				
Cooling method	Natural cooling				
Size (mm)	600 * 300 * 190	Net size			
Weight (kg)	15KG	Net weight			
	Battery module				
Product model number	TDDM51.2-52				
Rated voltage (V)	51.2				
Rated capacity (Ah)	52				
Maximum charging voltage (V)	57.6				
Maximum protection voltage of charge (V)	58.4				
Minimum protection voltage V	40				
Maximum charging current (A)	50				
Standard charging current (A)	25				

discharge current (A)	50	
Peak discharge current (A)	75	
Size mm	600 * 300 * 170	
Weight KG	31	
	Base	
Size	595 * 295 * 40	
Weight KG	5	



18858073356

tony@qygen.com

**b**atteriesback-up.com